



K 171 MK II

- **Professional hi-fi stereo studio headphones**
- **Self-adjusting headband for optimum fit**
- **Patented Varimotion speakers**
- **High ambient noise attenuation**
- **For broadcast and DJ use**
- **Rugged construction for tough handling**
- **Leatherette ear pads and additional velvet ear pads**
- **Single-sided, detachable 3 m cable and additional 5 m coiled cable**

The newly designed K 171 MK II combines the benefits of a closed-back design with the lightweight and comfort of supra-aural headphones.

The K 171 MK II is an excellent choice for DJ and broadcast applications where no sound can bleed from the headphones into live microphones.

The closed-back, loud and rugged design gives the K 171 MK II a different low-frequency character and maintains its comfort and flexibility.

Specifications

Type	closed-back, dynamic headphones
Sensitivity	94 dB/mW, 107 dB/V
Frequency range	18 to 26,000 Hz
Rated impedance	55 ohms
Max. input power	200 mW
Earpads	leatherette and velvet
Cable	3 m single-sided and 5 m coiled cable (99,9% oxygen-free); plug-in cable on headphones (mini-XLR connector)
Connector	gold plated stereo mini jack
Adapter	gold plated 1/8" to 1/4" screw-on adapter
Net weight (without cable)	200 g (7.1 oz.)
Shipping weight	500 g (17.6 oz.)
Patent(s)	Varimotion multiple-thickness diaphragm for dynamic transducer (Patent no. AT 403.751, US 6,185,809, EP 814.637 (DE, DK, FI, FR, GB, IT, NL), JP 3.927.651); Acoustics slot resistor for dynamic transducer (Patent no. AT 408.706, US 6,639,991, ZL 01116806)



Engineer's specifications

Supraaural, closed-back headphones with self-adjusting headband; Applications: Professional, portable stereo-headphones for monitoring and broadcast applications; Frequency range: 1826.000 Hz; Sensitivity: 94 dB at 1 mW / 107 dBV; impedance: 55 ohms per channel; power handling capability: 200 mW; Cable: 3 m and 5 m (OFC) single-sided, plug-in, easily replaceable cable with mini-XLR connector and with hard-gold plated, screwable 1/4" jack plug; Net (headphones without cable)/shipping weight: 200/500 g (7.1 /17.6 oz.).