



## **K 271 MK II**

- **Professional circumaural hi-fi stereo studio headphones**
- **Self-adjusting headband for optimum fit**
- **Patented Varimotion speakers**
- **High noise attenuation**
- **For onstage and studio use**
- **Automute feature mutes headphones when they are taken off**
- **Leatherette and additional velvet ear pads**
- **Single-sided, detachable 3 m cable and additional 5 m coiled cable**

The newly designed AKG legend, K 271 MK II combines the benefits of AKG's circumaural design for extreme comfort and a closed-back design for maximum isolation from ambient noise. Thanks to its XXL transducers, the K 271 MK II sounds clean, smooth and very rich.

The K 271 MK II is the perfect choice for any application where sonic bleed could cause problems such as broadcast work.

Another important feature of the K 271 MK II is the addition of a switch in the headband that mutes the audio just as soon as the headphones are taken off.

## **Specifications**

<b>Type</b>	closed-back, dynamic headphones
<b>Sensitivity</b>	91 dB/mW, 104 dB/V
<b>Frequency range</b>	16 to 28,000 Hz
<b>Rated impedance</b>	55 ohms
<b>Max. input power</b>	200 mW
<b>Earpads</b>	leatherette und velvet
<b>Cable</b>	3 m single-sided and 5 m coiled cable (99,9% oxygen-free); plug-in cable on headphones (mini-XLR connector)
<b>Connector</b>	gold plated stereo mini jack
<b>Adapter</b>	gold plated 1/8" to 1/4" screw-on adapter
<b>Net weight (without cable)</b>	240 g (8.5 oz.)
<b>Shipping weight</b>	550 g (19.4 oz.)
<b>Patent(s)</b>	Varimotion multiple-thickness diaphragm for dynamic transducer (Patent no. AT 403.751, US 6,185,809, EP 814.637 (DE, DK, FI, FR, GB, IT, NL), JP 3.927.651); Acoustics slot resistor for dynamic transducer (Patent no. AT 408.706, US 6,639,991, ZL 01116806)



## Engineer's specifications

Circumaural, closed-back headphones with self-adjusting headband and auto-shut-off feature;

Applications: Professional stereo-studio-headphones for live sound and studio monitoring;

Frequency range: 1628.000 Hz; Sensitivity: 91 dB at 1 mW / 104 dBV; impedance: 55 ohms per channel; power handling capability: 200 mW; Cable: 3 m and 5 m (OFC) single-sided, plug-in, easily replaceable cable with mini-XLR connector and with hard-gold plated, screwable 1/4" jack plug; Net (headphones without cable)/shipping weight: 240/550 g (8.4/19.2 oz.).