

ideas in motion



▶ 75 mm ▶ (H)DV

new!

FSB 4 Tech Specs



works with
SOOM






fluid heads
tripods
pedestals
lighting
camera stabilizing systems

▶ Quicklink: www.sachtler.com/en/fsb


▶ 75 mm ▶ (H)DV

FSB 4

Secure creativity

-  Payload range: 0 – 4 kg / 0 – 9 lb
-  Counterbalance: 5 steps +0
-  3 horizontal and 3 vertical grades of drag, +0
-  Tilt range: +90° to – 70°
-  For tripods with 75 mm bowls, integrated flat base fitting

- Long sliding range of camera plate
- Robust, metal housing
- Damping components featured in the range of larger fluid heads
- Only available in system




PAYLOAD TABLE


| C.O.G.* | min. kg/lb | max. kg/lb |
|---------|------------|------------|
| 50/2 | 0/0 | 3.9/8.5 |
| 75/3 | 0/0 | 3.2/7.0 |
| 100/4 | 0/0 | 2.7/5.9 |
| 125/5 | 0/0 | 2.3/5.1 |

*Center of gravity height (mm/in)

PAYLOAD DIAGRAM



DAMPING



CODE

▶ O307

SYSTEMS*

- FSB 4
- FSB 4 / 2 D
- FSB 4 MD
- FSB 4 / 2 MD
- FSB 4 SL MCF
- SOOM FSB 4

- FSB 4 PowerSet
- FSB 4 / 2 D PowerSet
- FSB 4 MD PowerSet
- FSB 4 / 2 MD PowerSet
- FSB 4 SL MCF PowerSet

*US do not sell ground spreaders.



ACCESSORIES



▶ Quicklink: www.sachtler.com/en/fsb